

Sicherheitsdatenblatt

gemäß 1907/2006/EG, Artikel 31

Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

* ABSCHNITT 1: Bezeichnung des Stoffs bzw. des Gemischs und des Unternehmens

- **1.1 Produktidentifikator**
- **Handelsname: Multi-7-Feinpflege**
- **Artikelnummer: LOS40**
- **1.2 Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird**
Keine weiteren relevanten Informationen verfügbar.
- **Verwendung des Stoffes / des Gemisches: Schmiermittel/ Schmierstoffe**
- **1.3 Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt**
- **Hersteller/Lieferant:**
EURO-LOCK Vertriebs-GmbH
Nordweststraße 3
D-59387 Ascheberg
Tel.: +49 (0) 2593 95887-0
Fax.: +49 (0) 2593 95887-29
www.euro-lock.de
- **Auskunftgebende Bereich:**
E-Mail: info@euro-lock.de
Tel.: +49 (0) 2593 95887-0
- **1.4 Notrufnummer: +49 (0) 2593 95887-0.**
- **Montag - Donnerstag 8.00 - 17.00 Uhr, Freitag 8.00 - 13.00 Uhr**

* ABSCHNITT 2: Mögliche Gefahren

- **2.1 Einstufung des Stoffs oder Gemischs**
- **Einstufung gemäß Verordnung (EG) Nr. 1272/2008**



GHS02 Flamme

Flam. Aerosol 1 H222-H229 Extrem entzündbares Aerosol. Behälter steht unter Druck: kann bei Erwärmung bersten.



GHS07

Eye Irrit. 2 H319 Verursacht schwere Augenreizung.

Asp. Tox. 1 H304 Kann bei Verschlucken und Eindringen in die Atemwege tödlich sein.

- **Einstufung gemäß Richtlinie 67/548/EWG oder Richtlinie 1999/45/EG**



F+; Hochentzündlich

R12: Hochentzündlich.

R66: Wiederholter Kontakt kann zu spröder oder rissiger Haut führen.

- **Besondere Gefahrenhinweise für Mensch und Umwelt:**

Das Produkt ist kennzeichnungspflichtig auf Grund des Berechnungsverfahrens der "Allgemeinen Einstufungsrichtlinie für Zubereitungen der EG" in der letztgültigen Fassung.

Bei längerem oder wiederholtem Hautkontakt kann Dermatitis (Hautentzündung) durch die entfettende Wirkung des Lösungsmittels entstehen.

Gesundheitsschädlich: kann beim Verschlucken Lungenschäden verursachen.

- **Klassifizierungssystem:**

Die Klassifizierung entspricht den aktuellen EG-Listen, ist jedoch ergänzt durch Angaben aus der Fachliteratur und durch Firmenangaben.

- **2.2 Kennzeichnungselemente**

- **Kennzeichnung gemäß Verordnung (EG) Nr. 1272/2008**

Das Produkt ist gemäß CLP-Verordnung eingestuft und gekennzeichnet.

(Fortsetzung auf Seite 2)

Sicherheitsdatenblatt

gemäß 1907/2006/EG, Artikel 31

Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

Handelsname: Multi-7-Feinpflege Artikel-Nr.: LOS40

(Fortsetzung von Seite 1)

· Gefahrenpiktogramme


GHS02 GHS07

· Signalwort Gefahr
· Gefahrbestimmende Komponenten zur Etikettierung:

 Kohlenwasserstoffe, C10-C13, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten
 Weissöl

· Gefahrenhinweise

 H222-H229 Extrem entzündbares Aerosol. Behälter steht unter Druck: kann bei Erwärmung bersten.
 H319 Verursacht schwere Augenreizung.

· Sicherheitshinweise

P101 Ist ärztlicher Rat erforderlich, Verpackung oder Kennzeichnungsetikett bereithalten.

P102 Darf nicht in die Hände von Kindern gelangen.

P210 Von Hitze, heißen Oberflächen, Funken, offenen Flammen und anderen Zündquellen fernhalten. Nicht rauchen.

P211 Nicht gegen offene Flamme oder andere Zündquelle sprühen.

P251 Nicht durchstechen oder verbrennen, auch nicht nach Gebrauch.

P280 Schutzhandschuhe / Augenschutz / Gesichtsschutz tragen.

 P305+P351+P338 BEI KONTAKT MIT DEN AUGEN: Einige Minuten lang behutsam mit Wasser spülen.
 Vorhandene Kontaktlinsen nach Möglichkeit entfernen. Weiter spülen.

P410+P412 Vor Sonnenbestrahlung schützen. Nicht Temperaturen über 50 °C/122 °F aussetzen.

P501 Inhalt/Behälter der Problemabfallentsorgung zuführen.

· Zusätzliche Angaben:

EUH066 Wiederholter Kontakt kann zu spröder oder rissiger Haut führen.

Ohne ausreichende Lüftung Bildung explosionsfähiger Gemische möglich.

· 2.3 Sonstige Gefahren
· Ergebnisse der PBT- und vPvB-Beurteilung

 · **PBT:** Nicht anwendbar.

 · **vPvB:** Nicht anwendbar.

ABSCHNITT 3: Zusammensetzung/Angaben zu Bestandteilen

· 3.2 Gemische

 · **Beschreibung:** Gemisch aus nachfolgend angeführten Stoffen mit ungefährlichen Beimengungen.

· Gefährliche Inhaltsstoffe:

EG-Nummer: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Kohlenwasserstoffe, C10-C13, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten Xn R65 R66 ----- Asp. Tox. 1, H304	25-50%
CAS: 75-28-5 EINECS: 200-857-2 Indexnummer: 601-004-00-0	Isobutan F+ R12 Flam. Gas 1, H220; Press. Gas, H280	20-25%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27-xxxx	Weissöl Asp. Tox. 1, H304	20-25%
CAS: 74-98-6 EINECS: 200-827-9 Indexnummer: 601-003-00-5	Propan F+ R12 Flam. Gas 1, H220; Press. Gas, H280	10-20%

(Fortsetzung auf Seite 3)

Sicherheitsdatenblatt

gemäß 1907/2006/EG, Artikel 31









Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

Handelsname: Multi-7-Feinpflge Artikel-Nr.: LOS40

(Fortsetzung von Seite 2)

CAS: 106-97-8 EINECS: 203-448-7 Indexnummer: 601-004-00-0	Butan  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	2,5-10%
CAS: 110-25-8 EINECS: 203-749-3	Oleoylsarcosin  Xn R20;  Xi R38-41;  N R50  Eye Dam. 1, H318;  Aquatic Acute 1, H400;  Acute Tox. 4, H332; Skin Irrit. 2, H315	1,0-2,5%

· **Zusätzliche Hinweise:** Der Wortlaut der angeführten Gefahrenhinweise ist dem Abschnitt 16 zu entnehmen.

ABSCHNITT 4: Erste-Hilfe-Maßnahmen

- **4.1 Beschreibung der Erste-Hilfe-Maßnahmen**
- **Nach Einatmen:**
Frischlufzufuhr, bei Beschwerden Arzt aufsuchen.
Den Betroffenen an die frische Luft bringen und ruhig lagern.
- **Nach Hautkontakt:**
Sofort mit Wasser und Seife abwaschen und gut nachspülen.
Mit Produkt verunreinigte Kleidungsstücke unverzüglich entfernen.
- **Nach Augenkontakt:**
Augen mehrere Minuten bei geöffnetem Lidspalt unter fließendem Wasser spülen. Bei anhaltenden Beschwerden Arzt konsultieren.
- **Nach Verschlucken:** Kein Erbrechen herbeiführen, sofort Arzthilfe zuziehen.
- **4.2 Wichtigste akute und verzögert auftretende Symptome und Wirkungen**
Keine weiteren relevanten Informationen verfügbar.
- **4.3 Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung**
Keine weiteren relevanten Informationen verfügbar.

ABSCHNITT 5: Maßnahmen zur Brandbekämpfung

- **5.1 Löschmittel**
- **Geeignete Löschmittel:**
Schaum
Löschpulver
Kohlendioxid
- **Aus Sicherheitsgründen ungeeignete Löschmittel:** Wasser im Vollstrahl
- **5.2 Besondere vom Stoff oder Gemisch ausgehende Gefahren**
Kann explosive Gas-Luft-Gemische bilden.
Beim Erhitzen oder im Brandfalle Bildung giftiger Gase möglich.
Kohlenmonoxid und Kohlendioxid
- **5.3 Hinweise für die Brandbekämpfung**
- **Besondere Schutzausrüstung:** Umgebungsluftunabhängiges Atemschutzgerät tragen.
- **Weitere Angaben**
Gefährdete Behälter mit Wassersprühstrahl kühlen.
Brandrückstände und kontaminiertes Löschwasser müssen entsprechend den behördlichen Vorschriften entsorgt werden.

ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung

- **6.1 Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren**
Schutzausrüstung tragen. Ungeschützte Personen fernhalten.
Für ausreichende Lüftung sorgen.
Zündquellen fernhalten.
- **6.2 Umweltschutzmaßnahmen:**
Bei Eindringen in Gewässer oder Kanalisation zuständige Behörden benachrichtigen.

(Fortsetzung auf Seite 4)

Sicherheitsdatenblatt

gemäß 1907/2006/EG, Artikel 31

Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

Handelsname: Multi-7-Feinpflege Artikel-Nr.: LOS40

(Fortsetzung von Seite 3)

- Nicht in die Kanalisation/Oberflächenwasser/Grundwasser gelangen lassen.
- **6.3 Methoden und Material für Rückhaltung und Reinigung:**
Mit flüssigkeitsbindendem Material (Sand, Kieselgur, Säurebinder, Universalbinder, Sägemehl) aufnehmen.
Für ausreichende Lüftung sorgen.
- **6.4 Verweis auf andere Abschnitte** Informationen zur Entsorgung siehe Abschnitt 13.

ABSCHNITT 7: Handhabung und Lagerung

- **7.1 Schutzmaßnahmen zur sicheren Handhabung**
Für gute Belüftung/Absaugung am Arbeitsplatz sorgen.
Berührung mit den Augen und der Haut vermeiden.
- **Hinweise zum Brand- und Explosionsschutz:**
Zündquellen fernhalten - nicht rauchen.
Maßnahmen gegen elektrostatische Aufladung treffen.
Behälter steht unter Druck. Vor Sonnenbestrahlung und Temperaturen über 50 °C (z.B. durch Glühlampen) schützen. Auch nach Gebrauch nicht gewaltsam öffnen oder verbrennen.
Nicht gegen Flamme oder auf glühenden Gegenstand sprühen.
- **7.2 Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten**
- **Lagerung:**
- **Anforderung an Lagerräume und Behälter:**
An einem kühlen Ort lagern.
Die behördlichen Vorschriften für das Lagern von Druckgaspackungen sind zu beachten.
- **Zusammenlagerungshinweise:** Nicht erforderlich.
- **Weitere Angaben zu den Lagerbedingungen:** Vor Hitze und direkter Sonnenbestrahlung schützen.
- **Lagerklasse:**
- **Klassifizierung nach Betriebssicherheitsverordnung (BetrSichV):** -
- **7.3 Spezifische Endanwendungen** Keine weiteren relevanten Informationen verfügbar.

ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

- **Zusätzliche Hinweise zur Gestaltung technischer Anlagen:** Keine weiteren Angaben, siehe Abschnitt 7.

· 8.1 Zu überwachende Parameter

- **Bestandteile mit arbeitsplatzbezogenen, zu überwachenden Grenzwerten:**

75-28-5 Isobutan

AGW	Langzeitwert: 2400 mg/m ³ , 1000 ml/m ³ 4(II);DFG
-----	--

74-98-6 Propan

AGW	Langzeitwert: 1800 mg/m ³ , 1000 ml/m ³ 4(II);DFG
-----	--

106-97-8 Butan

AGW	Langzeitwert: 2400 mg/m ³ , 1000 ml/m ³ 4(II);DFG
-----	--

- **Zusätzliche Hinweise:** Als Grundlage dienen die bei der Erstellung gültigen Listen.

· 8.2 Begrenzung und Überwachung der Exposition

- **Persönliche Schutzausrüstung:**
- **Allgemeine Schutz- und Hygienemaßnahmen:**
Von Nahrungsmitteln, Getränken und Futtermitteln fernhalten.
Beschmutzte, getränkte Kleidung sofort ausziehen.
Vor den Pausen und bei Arbeitsende Hände waschen.
Gase/Dämpfe/Aerosole nicht einatmen.
Berührung mit den Augen und der Haut vermeiden.
- **Atenschutz:** Bei guter Raumbelüftung nicht erforderlich.

(Fortsetzung auf Seite 5)

Sicherheitsdatenblatt

gemäß 1907/2006/EG, Artikel 31

Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

Handelsname: Multi-7-Feinpflge Artikel-Nr.: LOS40

(Fortsetzung von Seite 4)

- **Empfohlenes Filtergerät für kurzzeitigen Einsatz:** Filter AX
- **Handschutz:**
Das Handschuhmaterial muss undurchlässig und beständig gegen das Produkt / den Stoff / die Zubereitung sein.
- **Handschuhmaterial**
Nitrilkautschuk
Empfohlene Materialstärke: $\geq 0,45$ mm
- **Durchdringungszeit des Handschuhmaterials**
 ≥ 240 min
Die genaue Durchbruchzeit ist beim Schutzhandschuhhersteller zu erfahren und einzuhalten.
- **Augenschutz:**



Dichtschließende Schutzbrille

- **Körperschutz:** Arbeitsschutzkleidung

ABSCHNITT 9: Physikalische und chemische Eigenschaften

- **9.1 Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften**
- **Allgemeine Angaben**
- **Aussehen:**

Form:	Aerosol
Farbe:	Farblos
Geruch:	Lösemittelartig
- **Zustandsänderung**

Schmelzpunkt/Schmelzbereich:	Nicht bestimmt.
Siedepunkt/Siedebereich:	Nicht anwendbar, da Aerosol.
- **Flammpunkt:** Nicht anwendbar, da Aerosol.
- **Zündtemperatur:** >200 °C
- **Explosionsgefahr:** Das Produkt ist nicht explosionsgefährlich, jedoch ist die Bildung explosionsgefährlicher Dampf-/Luftgemische möglich.
- **Dichte bei 20 °C:** 0,68451 g/cm³
- **Löslichkeit in / Mischbarkeit mit**

Wasser:	Nicht bzw. wenig mischbar.
Organische Lösemittel:	76,1 %
VOC (EU)	521,1 g/l
VOCV (CH)	76,12 %
- **9.2 Sonstige Angaben** Keine weiteren relevanten Informationen verfügbar.

ABSCHNITT 10: Stabilität und Reaktivität

- **10.1 Reaktivität**
- **10.2 Chemische Stabilität**
- **Thermische Zersetzung / zu vermeidende Bedingungen:**
Keine Zersetzung bei bestimmungsgemäßer Verwendung.
- **10.3 Möglichkeit gefährlicher Reaktionen** Keine gefährlichen Reaktionen bekannt.
- **10.4 Zu vermeidende Bedingungen** Keine weiteren relevanten Informationen verfügbar.
- **10.5 Unverträgliche Materialien:** Keine weiteren relevanten Informationen verfügbar.
- **10.6 Gefährliche Zersetzungsprodukte:**
Aldehyde

(Fortsetzung auf Seite 6)

Sicherheitsdatenblatt

gemäß 1907/2006/EG, Artikel 31

Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

Handelsname: Multi-7-Feinpflge Artikel-Nr.: LOS40

Kohlenmonoxid und Kohlendioxid

(Fortsetzung von Seite 5)

ABSCHNITT 11: Toxikologische Angaben

- 11.1 Angaben zu toxikologischen Wirkungen
- Akute Toxizität:

- Einstufungsrelevante LD/LC50-Werte:

Kohlenwasserstoffe, C10-C13, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rat)
--------	------	-------------------

75-28-5 Isobutan

Inhalativ	LC50/4 h	>50 mg/l (rat)
-----------	----------	----------------

74-98-6 Propan

Inhalativ	LC50/4 h	20 mg/l (rat)
-----------	----------	---------------

106-97-8 Butan

Inhalativ	LC50/4 h	658 mg/l (rat)
-----------	----------	----------------

- Primäre Reizwirkung:
- an der Haut: Keine Reizwirkung.
- am Auge: Reizwirkung.
- Sensibilisierung: Keine sensibilisierende Wirkung bekannt.
- Zusätzliche toxikologische Hinweise: Dämpfe wirken betäubend.

ABSCHNITT 12: Umweltbezogene Angaben

- 12.1 Toxizität

- Aquatische Toxizität:

Kohlenwasserstoffe, C10-C13, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten

EC50/48 h	>1000 mg/l (daphnia)
-----------	----------------------

8042-47-5 Weissöl

LC50	>5000 mg/l (rat)
------	------------------

110-25-8 Oleoylsarcosin

EC50/48 h	0,68 mg/l (daphnia)
-----------	---------------------

- 12.2 Persistenz und Abbaubarkeit Keine weiteren relevanten Informationen verfügbar.
- 12.3 Bioakkumulationspotenzial Keine weiteren relevanten Informationen verfügbar.
- 12.4 Mobilität im Boden Keine weiteren relevanten Informationen verfügbar.
- Ökotoxische Wirkungen:
- Bemerkung: Schädlich für Fische.
- Weitere ökologische Hinweise:
- Allgemeine Hinweise:
Wassergefährdungsklasse 1 (Selbsteinstufung): schwach wassergefährdend
Nicht unverdünnt bzw. in größeren Mengen in das Grundwasser, in Gewässer oder in die Kanalisation gelangen lassen.
schädlich für Wasserorganismen
- 12.5 Ergebnisse der PBT- und vPvB-Beurteilung
- PBT: Nicht anwendbar.
- vPvB: Nicht anwendbar.
- 12.6 Andere schädliche Wirkungen Keine weiteren relevanten Informationen verfügbar.

DE

(Fortsetzung auf Seite 7)

Sicherheitsdatenblatt

gemäß 1907/2006/EG, Artikel 31

Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

Handelsname: Multi-7-Feinpflege Artikel-Nr.: LOS40

(Fortsetzung von Seite 6)

ABSCHNITT 13: Hinweise zur Entsorgung

- **13.1 Verfahren der Abfallbehandlung**
- **Empfehlung:** Darf nicht zusammen mit Hausmüll entsorgt werden. Nicht in die Kanalisation gelangen lassen.

- **Europäisches Abfallverzeichnis**

16 05 04	gefährliche Stoffe enthaltende Gase in Druckbehältern (einschließlich Halonen)
----------	--

15 01 04	Verpackungen aus Metall
----------	-------------------------

- **Ungereinigte Verpackungen:**
- **Empfehlung:** Entsorgung gemäß den behördlichen Vorschriften.

ABSCHNITT 14: Angaben zum Transport

- **14.1 UN-Nummer**
- **ADR, IMDG, IATA** 1950

- **14.2 Ordnungsgemäße UN-Versandbezeichnung**
- **ADR** 1950 DRUCKGASPACKUNGEN
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **14.3 Transportgefahrenklassen**

- **ADR**



- **Klasse** 2 5F Gase
- **Gefahrzettel** 2.1

- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

- **14.4 Verpackungsgruppe**
- **ADR, IMDG, IATA** entfällt

- **14.5 Umweltgefahren:**
- **Marine pollutant:** Nein

- **14.6 Besondere Vorsichtsmaßnahmen für den Verwender** Achtung: Gase
- **Kemler-Zahl:** -
- **EMS-Nummer:** F-D,S-U

- **14.7 Massengutbeförderung gemäß Anhang II des MARPOL-Übereinkommens 73/78 und gemäß IBC-Code** Nicht anwendbar.

- **Transport/weitere Angaben:**

- **ADR**
- **Begrenzte Menge (LQ)** LQ2
- **Beförderungskategorie** 2

(Fortsetzung auf Seite 8)

Sicherheitsdatenblatt

gemäß 1907/2006/EG, Artikel 31

Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

Handelsname: Multi-7-Feinpflege Artikel-Nr.: LOS40

(Fortsetzung von Seite 7)

· Tunnelbeschränkungscode	D
· UN "Model Regulation":	UN1950, DRUCKGASPACKUNGEN, 2.1

ABSCHNITT 15: Rechtsvorschriften

- **15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch**
 - **Nationale Vorschriften:**
 - **Klassifizierung nach Betriebssicherheitsverordnung (BetrSichV): -**
 - **Technische Anleitung Luft:**
- | Klasse | Anteil in % |
|--------|-------------|
| NK | 50-100 |
- **Wassergefährdungsklasse: WGK 1 (Selbsteinstufung): schwach wassergefährdend.**
 - **15.2 Stoffsicherheitsbeurteilung: Eine Stoffsicherheitsbeurteilung wurde nicht durchgeführt.**

ABSCHNITT 16: Sonstige Angaben

Die Angaben stützen sich auf den heutigen Stand unserer Kenntnisse, sie stellen jedoch keine Zusicherung von Produkteigenschaften dar und begründen kein vertragliches Rechtsverhältnis.

- **Relevante Sätze**
- H220 Extrem entzündbares Gas.
H280 Enthält Gas unter Druck; kann bei Erwärmung explodieren.
H304 Kann bei Verschlucken und Eindringen in die Atemwege tödlich sein.
H315 Verursacht Hautreizungen.
H318 Verursacht schwere Augenschäden.
H332 Gesundheitsschädlich bei Einatmen.
H400 Sehr giftig für Wasserorganismen.
- R12 Hochentzündlich.
R20 Gesundheitsschädlich beim Einatmen.
R38 Reizt die Haut.
R41 Gefahr ernster Augenschäden.
R50 Sehr giftig für Wasserorganismen.
R65 Gesundheitsschädlich: kann beim Verschlucken Lungenschäden verursachen.
R66 Wiederholter Kontakt kann zu spröder oder rissiger Haut führen.
- **Abkürzungen und Akronyme:**
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organization
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Gas 1: Flammable gases, Hazard Category 1
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas: Gases under pressure: Compressed gas
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

(Fortsetzung auf Seite 9)

Sicherheitsdatenblatt
gemäß 1907/2006/EG, Artikel 31

Druckdatum: 02.10.2014

Versionsnummer 8

überarbeitet am: 02.10.2014

Handelsname: Multi-7-Feinpflge Artikel-Nr.: LOS40

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

· *** Daten gegenüber der Vorversion geändert**

(Fortsetzung von Seite 8)

DE

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.11.2014

Version number 8

Revision: 12.11.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *Multi-7-Feinpflege*
- **Article number:** *LOS40*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Lubricant*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
EURO-LOCK Vertriebs-GmbH
Nordweststrae 3
D-59387 Ascheberg
Tel.: +49 (0) 2593 95887-0
Fax.: +49 (0) 2593 95887-0
www.euro-lock.de
- **Further information obtainable from:**
Tel.: +49 (0) 2593 95887-0
E-Mail: info@euro-lock.de
- **1.4 Emergency telephone number:**
+49 (0) 2593 95887-0 Monday - Thursday 8:00 - 17:00 CET, Friday 8:00 - 13:00 CET

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



F+; Extremely flammable

R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or cracking.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Harmful: may cause lung damage if swallowed.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.11.2014

Version number 8

Revision: 12.11.2014

Više než 1000 výrobků [číslo výrobku] 1*1

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
White mineral oil

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 Dispose of contents/container to hazardous or special waste collection point.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.
Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Xn R65 R66 Asp. Tox. 1, H304	25-50%
CAS: 75-28-5 EINECS: 200-857-2	isobutane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	20-25%
CAS: 8042-47-5 EINECS: 232-455-8 Reg.nr.: 01-2119487078-27-xxxx	White mineral oil Asp. Tox. 1, H304	20-25%
CAS: 74-98-6 EINECS: 200-827-9	propane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	10-20%

(Contd. on page 3)









Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.11.2014

Version number 8

Revision: 12.11.2014

Trade name: Multi-7-Feinpflege

CAS: 106-97-8 EINECS: 203-448-7	butane  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	(Contd. of page 2) 2.5-10%
CAS: 110-25-8 EINECS: 203-749-3	Oleoylsarcosin  Xn R20;  Xi R38-41;  N R50  Eye Dam. 1, H318;  Aquatic Acute 1, H400;  Acute Tox. 4, H332; Skin Irrit. 2, H315	1.0-2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
Take affected persons into fresh air and keep quiet.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately remove any clothing soiled by the product.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Foam
Fire-extinguishing powder
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.11.2014

Version number 8

Revision: 12.11.2014

Trade name: Multi-7-Feinpflege

(Contd. of page 3)

- **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Avoid contact with skin and eyes.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Recommended filter device for short term use:** Filter AX
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- **Material of gloves**
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.45 mm
- **Penetration time of glove material**
 ≥ 240 min
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.11.2014

Version number 8

Revision: 12.11.2014

Trade name: Multi-7-Feinpflege

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

* **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Colour:	Colourless
Odour:	Solvent-like

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: Not applicable, as aerosol.

· Ignition temperature: >200 °C

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Density at 20 °C: 0.68451 g/cm³

· Solubility in / Miscibility with

water:	Not miscible or difficult to mix.
Organic solvents:	76.1 %
VOC (EC)	521.1 g/l

· 9.2 Other information: No further relevant information available.

* **SECTION 10: Stability and reactivity**

· 10.1 Reactivity

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions: No dangerous reactions known.

· 10.4 Conditions to avoid: No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

Aldehyde
Carbon monoxide and carbon dioxide

* **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

· Acute toxicity:

· LD/LC50 values relevant for classification:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.11.2014

Version number 8

Revision: 12.11.2014

Trade name: Multi-7-Feinpflege

(Contd. of page 5)

75-28-5 isobutane

Inhalative LC50/4 h >50 mg/l (rat)

74-98-6 propane

Inhalative LC50/4 h 20 mg/l (rat)

106-97-8 butane

Inhalative LC50/4 h 658 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:** Vapours have narcotic effect.

SECTION 12: Ecological information

· **12.1 Toxicity**· **Aquatic toxicity:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics**

EC50/48 h >1000 mg/l (daphnia)

8042-47-5 White mineral oil

LC50 >5000 mg/l (rat)

110-25-8 Oleoylsarcosin

EC50/48 h 0.68 mg/l (daphnia)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

16 05 04 gases in pressure containers (including halons) containing dangerous substances

15 01 04 metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.11.2014



Version number 8

Revision: 12.11.2014

Trade name: Multi-7-Feinpflege

(Contd. of page 6)

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es) · ADR	
	
· Class · Label	2 5F Gases. 2.1
· IMDG, IATA	
	
· Class · Label	2.1 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Gases. - F-D,S-U
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.11.2014

Version number 8

Revision: 12.11.2014

Trade name: **Multi-7-Feinpflege**

(Contd. of page 7)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H400 Very toxic to aquatic life.
- R12 Extremely flammable.
- R20 Harmful by inhalation.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- R50 Very toxic to aquatic organisms.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organization
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Compressed gas
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

· *** Data compared to the previous version altered.**